






Rain Pipes

-  **High product consistency:** Made by plastic extrusion and laser punched on the production line, Plentirain rain pipe is with a stable quality and homogeneous water spraying.
-  **Long service life:** Plentirain Rain Pipe has the advantage as UV-protection, Anti-clogging, Anti-aging, good tension resistance. The service life is about 2-5 years, depending on use and maintain condition.
-  **Low working pressure:** Plentirain Rain pipe can works stable at 0.2 bar -0.8 bar. It saves energy over 20% than sprinkler irrigation.



Model	Width (mm)	Dia. (mm)	Wall thick (mm)	Holes qty/set	Hole set spacing (cm)	Flow rate (m ³ /hr/10 m)	Max. running length (m)	Spray range at two sides	Working pressure (bar)	Roll length (m)	Caron size(cm)	Rolls/ ctn
PRSTN2002	32	20	0.2	2/3/5/7/9	10-40	0.7	20	1.25m each side	0.2-0.8	200	36*36*24	5
PRSTN2502	40	25	0.2	2/3/5/7/9	10-40	0.9	25	1.5m each side	0.2-0.8	200	36*36*28	5
PRSTN28018	45	28.5	0.18	2/3/5/7/9	10-40	1.4	30	1.75m each side	0.2-0.8	200	36*36*31	5
PRSTN2802	45	28.5	0.2	2/3/5/7/9	10-40	1.4	30	1.75m each side	0.2-0.8	200	36*36*31	5
PRSTN32018	50	32	0.18	2/3/5/7/9	10-40	1.55	50	2m each side	0.2-0.8	200	36*36*33	5
PRSTN3202	50	32	0.2	2/3/5/7/9	10-40	1.55	50	2m each side	0.2-0.8	200	36*36*33	5
PRSTN4002	63	40	0.2	2/3/5/7/9	10-40	1.6	60	2.5m each side	0.2-0.8	200	36*36*33	4
PRSTN4003	63	40	0.3	2/3/5/7/9	10-40	1.6	60	2.5m each side	0.2-0.8	100	33*33*36	5
PRSTN4004	63	40	0.4	2/3/5/7/9	10-40	1.6	60	2.5m each side	0.2-0.8	100	36*36*38	5
PRSTN5003	80	50	0.3	2/3/5/7/9	10-40	2.2	80	4m each side	0.2-0.8	120	36*36*35	4
PRSTN5004	80	50	0.4	2/3/5/7/9	10-40	2.2	80	4m each side	0.2-0.8	100	36*36*35	4
PRSTN6303	100	63	0.3	2/3/5/7/9	10-40	3.1	100	5m each side	0.2-0.8	120	36*36*35	3
PRSTN6304	100	63	0.4	2/3/5/7/9	10-40	3.1	100	5m each side	0.2-0.8	100	36*36*35	3



Wings Rain Pipe

Wings Ring Pipe makes up by 1 main rain pipe with 2 wings at both sides, the wings can protect the main hose from being scratched by sharp objects or bitten by animals. The wings also keep the main hose balanced.



Model	Dia. (inch)	Hose width (mm)	Wing width each side (mm)	Total width (mm)	Wall thick (mm)	Spray range at two sides	Running length (m)	Working pressure (bar)	Flow rate (m ³ /hr/10m)	Roll length	Rolls/Ctn	Carton size (cm)	Weight/Ctn (kg)
PRSTD2523	1" (25mm)	45mm	5mm	55mm	0.23	2m each side	30	0.5-0.8	0.9	100m/roll	5	44*44*29	12.6
PRSTD3225	1-1/4" (32mm)	50mm	6mm	62mm	0.25	2.5m each side	50	0.5-0.8	1.55	100m/roll	5	46*46*33	15.2
PRSTD4030	1-1/2" (40mm)	63mm	6mm	75mm	0.3	3m each side	60	0.5-0.8	1.6	100m/roll	4	50*50*31	17.54
PRSTD5035	2" (50mm)	80mm	8mm	96mm	0.35	4m each side	80	0.5-0.8	2.2	100m/roll	3	54*54*31	19.6
PRSTD6335	2-1/2" (63mm)	100mm	8mm	116mm	0.35	5m each side	100	0.5-0.8	3.1	100m/roll	3	60*60*37	23.5