



Manually Controlled Valve

Photo	Product code	SPECIFICATION	Quantity (Pcs/Ctn)	Carton Size (cm)	G.W. (kg/Ctn)
	DSF-1.5M-B	Manual override Material: Reinforced Nylon 1 1/2" BSP Max. Flow rate: 25m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	1	17X16X22	1.29
	DSF-2M-B	Manual override Material: Reinforced Nylon 2" BSP Max. Flow rate: 40m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	1	17X16X22	1.29
	DSF-3M-B	Manual override Material: Reinforced Nylon 3" BSP Max. Flow rate: 90m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	1	20X20X28	2.2
	DSF-3M-S	Manual override Material: UPVC 3" Solvent Welding Max. Flow rate: 100m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	1	27X26X29	5.7
	DSF-4M-S	Manual override Material: UPVC 4" Solvent Welding Max. Flow rate: 160m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	1	27X26X29	5.7
/	DSF-6M-S	Manual override Material: UPVC 6" Solvent Welding Max. Flow rate: 350m ³ /h, Max. Working pressure: 10bar,Min. pressure: 0.69bar	/	/	/